

Specifications

HP / kW	2.5 / 1.9	3.5 / 2.6
Engine type	1 cylinder	
Displacement (CID/CC)	5.2 / 85	
Full throttle RPM	2.5	5000-5500 3.5 5000-6000
Fuel induction system	2-valve pushrod (overhead valve)	
Recommended fuel	87% octane / up to 10% ethanol	
Recommended oil	Mercury FourStroke Oil 10W-30	
Engine protection operator warning system	Over-rev	
Starting	Manual	
Steering	Tiller with 360° turning	
Shaft length	2.5	15" / 381 mm 3.5 15" / 381 mm 20" / 508 mm
Gearcase ratio	2.15:1	
Dry weight *Lightest model available	38 lbs / 17 kg	
CARB star rating	3	
Bore and stroke	2.16 x 1.42" / 55 x 36 mm	
Ignition	CDI w/electronic spark advance	
Fuel system	Carbureted	
Cooling system	Water-cooled with thermostat	
Gear shift	F-N	
Trim system	4 position	
Trim positions	4	
Exhaust system	Above prop	
Shallow water trim range (degrees)	16	
Integrated fuel tank (gal / L)	0.3 / 1.1	
Color	Phantom Black	



2.5 - 3.5 hp FourStroke

Handheld Reliability





2.5-3.5 hp FourStroke

Lightweight.

Weighing just 38 and 57 pounds, respectively, our 2.5 - 3.5hp and 4 - 6hp FourStroke outboards are easy to lift and carry.



Shallow Water.

Multiple trim positions enhance performance and enable shallow water operation.



Easy to Start.

Automatic decompression bleeds off cylinder pressure to reduce the pulling force required to start the engine.



Safe Portability & Storage.

1 Liter integral fuel tank with external fuel shutoff valve that prevents spillage. Engine can be laid on three sides for storage.



Precise Control.

Mercury 2.5 and 3.5hp FourStroke engines feature neutral-forward shifting with 360-degree steering for full thrust in all directions.

Long Tiller Handle with Twist Throttle

Includes throttle friction adjustment for comfort and easily adjusted steering friction offering better steering response.